


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTIONS IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	CHANGED BY
A	DRAWING REPLACES DGFC15MF-OD1	9/25/14	D. DESJARDIN



RECOMMENDED
PANEL OPENING
MAX PANEL THICKNESS: 0.06"

NOTES:

MATERIALS:

SHELL: COLD ROLLED STEEL
CONTACTS: BRASS
INSULATOR: PBT UL94-V0 RATED

FINISH:

SHELL: TIN PLATED
CONTACT: GOLD FLASH

ELECTRICAL:

CONTACT CURRENT RATING: 5.0 AMP MAX
OPERATING VOLT: 100 VDC
INSULATION RESISTANCE: 500 MΩ @100 VDC
DIELECTRIC WITHSTAND: 500 VDC, 1 MINUTE
INDIVIDUAL CAPACITANCE ON EACH PIN: 820pF

APPLICATION NOTES:

ALL PINS WIRED STRAIGHT THROUGH
ALL-METAL HOUSING PROVIDES 100% SHIELDING

LABELING:



PANTONE 2945 BLUE. "L-COM" FONT MyriaMM ITALIC.
"CAPACITIVE FILTER" FONT ARIAL BOLD, TEXT HEIGHTS; .085"
TEXT COLOR; WHITE.

PACKAGING:



COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:



CE2011/65/EU(RoHS DIRECTIVE)



FEMALE, 15 PIN
D-SUB CONNECTOR




JACKSCREW
SPECIFICATION




CAPACITIVE FILTER

ALL PINS — ALL PINS

820 pf±10%
CERAMIC CAPACITOR
VOLTAGE 100 VDC



UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]
OVERALL CABLE LENGTH TOLERANCE:
≤12 [305] = +1 [25] / -0
>12 [305] ≤60 [1524] = +2(51) / -0
>60 [1524] ≤120 [3048] = +4 [102] / -0
>120 [3048] ≤300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0%
ALL OTHER DIMENSIONAL TOLERANCES:
X = ±.2 [5.08]
.XX = ±.02 [5.1]
.XXX = ±.005 [1.3]



APPROVALS	DATE
DRAWN BY R.CARRICK	09/28/02
CHECKED BY T.CLARK	09/28/02
APPROVED BY D.PARHAM	09/28/02

L-com Global Connectivity
45 BEECHWOOD DRIVE
NORTH ANDOVER, MA
01845

CATEGORY: D-SUBMINIATURE

PRODUCT DESCRIPTION: ADPT, DB15M/F CAP FILTER

SIZE	FSCM NO.	DWG. NO.	REV.
B	43321	DGFC15MF	A

SCALE: 2:1 CAD FILE: DGFC15MF.SLDDRW SHEET 1 OF 1